

DECLARATION OF PERFORMANCE

No: 003

1. Unique identification code of the product

DRY-PRESSED CERAMIC TILES, WITH WATER ABSORTION $3\% < E \leq 6\%$, TYPE 3

2. Intended use

FOR INTERNAL FLOORINGS

3. Name and adress of Manufacturer

BALDOCER CERAMICAS, S.A.
Ctra. Pobla de Tornesa – Vall d'Alba, km.4
12192 Vilafamés (Castellón) SPAIN

4. Systems of AVCP

4

5. Name and number of laboratory notified

NOT APPLY

6. Declared performances

ESSENTIAL CHARACTERISTICS	PERFORMANCES	TECHNICAL SPECIFICATION HARMONIZED
Reaction to fire	A1 _{fl}	EN 14411: 2012
Release of dangerous substance, for: - Cadmium - Lead - Others	NPD	
Breaking strength	>1000	
Slipperiness, as: Pendulum method according to ET CEN/TS 16165	>35	
Thermal shock	NPD	
Durability for: - Internal use - External Use	Pass NPD	
Tactility	NPD	

The performance of the product identified in point 1 is in conformity with the set of declared in point 6.

This declaration of conformity is issued under the sole responsibility of the manufacturer indicated in point 3.

Felipe Peraire Palos
General Manager

BALDOCER, S.A.

P.P.

Vilafamés, June 27th, 2013