

DECLARATION OF PERFORMANCE

No: 006

1. Unique identification code of the product

DRY-PRESSED CERAMIC TILES, WITH WATER ABSORTION $E \leq 0.5\%$, TYPE 6

2. Intended use

FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS

3. Name and adress of Manufacturer

BALDOCER CERAMICAS, S.A.
Ctra. Pobla Tornesa – Vall d'Alba, km.4
12192 Vilafamés (Castellón) SPAIN

4. Systems of AVCP

4

5. Name and number of laboratory notified

NOT APPLY

6. Declared performances

| ESSENTIAL CHARACTERISTICS | PERFORMANCES | TECHNICAL SPECIFICATION HARMONIZED |
|---|---|------------------------------------|
| Reaction to fire | A1-A1 _{FL} | |
| Release of dangerous substance, for: - Cadmium - Lead - Others | NPD | |
| Breaking strength | >1300 | |
| Slipperiness, as: Pendulum method according to ET CEN/TS 16165 | >35 | EN 14411: 2012 |
| Adhesion (N/mm ²) | >1 Nw/mm ² with type C2 adhesives | |
| Thermal shock | Pass | |
| Durability for: - Internal use - External Use | Pass Pass | |
| Tactility | NPD | |

The performance of the product identified in point 1 is in conformity with the set of declared in point 6.

This declaration of conformity is issued under the sole responsibility of the manufacturer indicated in point 3.

Felipe Peraire Palos
General Manager

Vilafamés, June 27th, 2013


BALDOCER, S.A.
S.A.
www.baldocer.com